



modello/model  
**SPCL 18 o 23**  
**PROFESSIONAL**



Spaccalegna modello SPCL 18 ton. o 23 ton.  
modello Professional PTO oppure 220 o 380 Volt  
oppure combinata PTO + elettrica 220 o 380 volt  
con braccio caricatronchi e cuneo obliquo



Logsplitter model SPCL 18 ton. or 23 ton  
Professional model PTO or electrical 220 o 380 Volt  
or combined PTO + electrical 220 or 380 volt with  
loading arm and oblique knife



### SCHEDA TECNICA/DATA SHEET SPECIFICATION

Ingombro mm l x p x h

Measures mm l x w x h

Peso Kg (variabile con accessori)

Weight Kg (variable with accessories)

Corsa cilindro

Stroke cylinder

Spinta/ Push

Distributore/ Distributor

Tempo di ciclo/ Cycle work

Motore per versione elettrica

Motor for electric version

Optional

Optional

1000 x 1400 x 2750 (h 2150 chiuso)

1000 x 1400 x 2750 (h 2150 closed)

Mod. 18: Kg 670 • Mod. 23: Kg 750

mm 1100

18/23 Ton.

Autospeed a 2 velocità • Autospeed 2 speed

Mod. 18: Discesa: 25 cm/sec; Salita: 26cm/sec;

Mod. 23: Discesa: 23 cm/sec; Salita: 21 cm/sec.

Mod. 18: To go down: 25 cm/sec; To go up: 26 cm/sec;

Mod. 23: To go down: 23 cm/sec; To go up: 21 cm/sec

Mod. 18: 380 Volt HP 7,5 • Mod. 23: 380 Volt HP 7,5

Verricello idraulico con comando manuale o con

radiocomando • Ruote ad aria e timone

motore Honda GX 390 su carrellino omologato

Hydraulic winch with manual control or with

radiocontrol • Air wheels and drawbar

honda gx390 engine on approved trolley